

# UNISTEEL® G169 RSA®

## Long-Wearing Radial For All-Position Service

- Straight ribs and a flat tread radius provide uniform wear
- A strong shoulder rib increases stiffness to reduce cupping and wear
- Penetration protectors help to resist cuts and punctures for increased durability

TIRE SIZE	LOAD RANGE	TREAD DEPTH 32NDS INCH	DESIGN RIM WIDTH	MINIMUM DUAL SPACING IN [MM]		INFLATED DIMENSIONS					
						OVERALL WIDTH IN [MM]		OVERALL DIAMETER IN [MM]		STATIC LOADED RADIUS IN [MM]	
TUBELESS TIRES ON 15° DROP CENTER RIMS											
285/75R24.5	G	20	8.25	12.5	[318]	11.1	[282]	41.6	[1057]	19.5	[495]
255/70R22.5	H	18	7.50	11.3	[287]	10.0	[254]	36.7	[932]	17.1	[434]
275/70R22.5	H	18	7.50	11.9	[302]	10.4	[264]	37.7	[958]	17.6	[447]
295/75R22.5	G	20	8.25	12.9	[328]	11.1	[282]	40.5	[1029]	18.9	[480]

TIRE SIZE	REVS PER MILE [KM]		TIRE WEIGHT LB [KG]		MAXIMUM LOAD @ INFLATION								SPEED RATING (MPH)
					SINGLE				DUAL				
TUBELESS TIRES ON 15° DROP CENTER RIMS													
285/75R24.5	499	[310]	122	[55]	6175	110	[2800	760]	5675	100	[2575	690]	75
255/70R22.5	566	[352]	92	[42]	5510	120	[2500	830]	5070	120	[2300	830]	81
275/70R22.5	551	[342]	106	[48]	6940	125	[3150	860]	6395	125	[2900	860]	75
295/75R22.5	513	[319]	120	[54]	6175	110	[2800	760]	5675	100	[2575	690]	75

Steel/Steel Construction

## CLASS A

